spraying it with water or applying a nontoxic emollient:

- (2) Assuring that the pectoral flippers (when applicable) are allowed freedom of movement at all times;
- (3) Making adjustments in the position of the mammal when necessary to prevent necrosis of the skin at weight pressure points; and
- (4) Calming the mammal to prevent struggling, thrashing, and other activity that may cause overheating or physical trauma.
- (b) Unless otherwise directed by a shipper or authorized representative, at least one-half of the floor area in a primary enclosure used to transport sea otters to the United States shall contain sufficient crushed ice or ice water to provide each otter with moisture necessary to maintain its hair coat by preventing it from drying and to minimize soiling of the hair coat with urine and fecal material.
- (c) A marine mammal exhibiting excited or otherwise dangerous behavior shall not be taken from its primary enclosure except under extreme emergency conditions and then only by the shipper or other authorized individual who is capable of handling the animal safely.

SPECIFICATIONS FOR ELEPHANTS AND UNGULATES

§14.141 Consignment to carrier.

Species that grow antlers shall not be accepted for transport unless the antlers have been shed or surgically removed.

§14.142 Primary enclosures.

(a) Except as provided in §14.106(j), ventilation openings must be located on at least two walls of a primary enclosure. When the required ventilation openings are located on two opposite walls of the primary enclosure, these ventilation openings shall comprise at least 16 percent of the total surface area of each ventilated wall. When ventilation openings are located on all four walls of the primary enclosure, the openings shall comprise at least 8 percent of the total surface area of each wall. At least one-third of the minimum area required for ventilation shall be located on the lower one-half

- of the primary enclosure and at least one-third of the total minimum area required for ventilation shall be located on the upper one-half of the primary enclosure.
- (b) No more than one elephant or ungulate shall be transported in a primary enclosure, except that: a mother and nursing young may be shipped in the same primary enclosure if the shipment complies with the provisions of §14.105(b); in the case of land or sea transport, a pair of juvenile elephants or ungulates or other pairs that have been habitually housed together may be shipped in the same primary enclosure.
- (c) A primary enclosure used to transport an elephant or ungulate shall be large enough to allow the animal to lie or stand in a natural upright position with the head extended, but not large enough for the animal to roll over.
- (d) A primary enclosure used to transport an elephant or ungulate with horns or tusks shall be designed and constructed to prevent the horns or tusks from becoming trapped or injuring the animal itself, other animals nearby, attendants, or cargo handlers.
- (e) A primary enclosure for an elephant or ungulate shall be equipped with a removable water trough that can be securely hung within the enclosure above the floor and can be filled from outside the enclosure.

SPECIFICATIONS FOR SLOTHS, BATS, AND FLYING LEMURS (CYNOCEPHALIDAE)

§14.151 Primary enclosures.

(a) Except as provided in §14.106(j), ventilation openings must be located on at least two walls of a primary enclosure. When the required ventilation openings are located on two opposite walls of the primary enclosure, these ventilation openings shall comprise at least 16 percent of the total surface area of the ventilated wall. When ventilation openings are located on all four walls, the openings shall comprise at least 8 percent of the total surface area of each wall. At least one-third of the total minimum area required for ventilation of the primary enclosure shall be located on the upper one-half of the primary enclosure.